

PG 11B 03/06164 NL 030084

Rec'd PCT/PTO 20 JUL 2005 CT  
10/542905

REGISTRY OF PATENTS  
SINGAPORE

This is to certify that the annexed is a true copy of the following international application as filed with the Registry as the receiving Office and of any corrections thereto.

Date of Filing : 24 JAN 2003

Application Number : PCT/SG03/00020

Applicant(s) /  
Proprietor(s) of Patent : PHILIPS ELECTRONICS SINGAPORE PTE  
LTD; KONINKLIJKE PHILIPS  
ELECTRONICS N.V.

Title of Invention : DISPLAY DEVICE COMPRISING A  
CATHODE RAY TUBE

**PRIORITY  
DOCUMENT**

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)


REC'D 05 FEB 2004

WIPO PCT

  
Chig Kam Tack  
Senior Assistant Registrar  
for REGISTRAR OF PATENTS  
SINGAPORE

6 Dec 2003

Best Available Copy



HOME COPY

1/3

PNL030084WOP

## PCT REQUEST

Original (for SUBMISSION) - printed on 23.01.2003 11:28:24 AM

0	For receiving Office use only	
0-1	International Application No.	PCT/SG 0 3 / 0 0 0 20
0-2	International Filing Date	2 4 JAN 2003 (24-01-03)
0-3	Name of receiving Office and "PCT International Application"	REGISTRY OF PATENTS (SINGAPORE) PCT INTERNATIONAL APPLICATION
0-4	Form - PCT/RO/101 PCT Request	
0-4-1	Prepared using	PCT-EASY Version 2.92 (updated 01.01.2003)
0-5	Petition The undersigned requests that the present international application be processed according to the Patent Cooperation Treaty	
0-6	Receiving Office (specified by the applicant)	Intellectual Property Office of Singapore (RO/SG)
0-7	Applicant's or agent's file reference	PNL030084WOP
I	Title of invention	DISPLAY DEVICE COMPRISING A CATHODE RAY TUBE
II	Applicant	
II-1	This person is:	applicant only
II-2	Applicant for	SG
II-4	Name	PHILIPS ELECTRONICS SINGAPORE PTE LTD
II-5	Address:	Attn. Mr J.C. De Visser 620A Lorong 1 Toa Payoh TP2-2nd Floor 319762 Singapore Singapore
II-6	State of nationality	SG
II-7	State of residence	SG
II-8	Telephone No.	+65 7995021
II-9	Facsimile No.	+65 7995022
III-1	Applicant and/or inventor	
III-1-1	This person is:	applicant only
III-1-2	Applicant for	all designated States
III-1-4	Name	KONINKLIJKE PHILIPS ELECTRONICS N.V.
III-1-5	Address:	Groenewoudseweg 41 NL-5621 BA Eindhoven Netherlands
III-1-6	State of nationality	NL
III-1-7	State of residence	NL
III-1-8	Telephone No.	+31 40 2743444
III-1-9	Facsimile No.	+31 40 2743489

CONFIRMATION COPY

## PCT REQUEST


PNL030084WOP

Original (for SUBMISSION) - printed on 23.01.2003 11:28:24 AM

<b>V</b>	<b>Designation of States</b>		
<b>V-1</b>	Regional Patent (other kinds of protection or treatment, if any, are specified between parentheses after the designation(s) concerned)	EP: AT BE BG CH&LI CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL PT SE SI SK TR and any other State which is a Contracting State of the European Patent Convention and of the PCT	
<b>V-2</b>	National Patent (other kinds of protection or treatment, if any, are specified between parentheses after the designation(s) concerned)	SG	
<b>V-5</b>	<b>Precautionary Designation Statement</b> In addition to the designations made under Items V-1, V-2 and V-3, the applicant also makes under Rule 4.9(b) all designations which would be permitted under the PCT except any designation(s) of the State(s) indicated under Item V-6 below. The applicant declares that those additional designations are subject to confirmation and that any designation which is not confirmed before the expiration of 15 months from the priority date is to be regarded as withdrawn by the applicant at the expiration of that time limit.		
<b>V-6</b>	<b>Exclusion(s) from precautionary designations</b>	NONE	
<b>VI</b>	<b>Priority claim</b>	NONE	
<b>VII-1</b>	<b>International Searching Authority Chosen</b>	European Patent Office (EPO) (ISA/EP)	
<b>VIII</b>	<b>Declarations</b>	Number of declarations	
<b>VIII-1</b>	Declaration as to the identity of the inventor	-	
<b>VIII-2</b>	Declaration as to the applicant's entitlement, as at the international filing date, to apply for and be granted a patent	-	
<b>VIII-3</b>	Declaration as to the applicant's entitlement, as at the international filing date, to claim the priority of the earlier application	-	
<b>VIII-4</b>	Declaration of inventorship (only for the purposes of the designation of the United States of America)	-	
<b>VIII-5</b>	Declaration as to non-prejudicial disclosures or exceptions to lack of novelty	-	
<b>IX</b>	<b>Check list</b>	number of sheets	electronic file(s) attached
<b>IX-1</b>	Request (including declaration sheets)	3	-
<b>IX-2</b>	Description	6	-
<b>IX-3</b>	Claims	2	-
<b>IX-4</b>	Abstract	1	EZABST00.TXT
<b>IX-5</b>	Drawings	3	-
<b>IX-7</b>	<b>TOTAL</b>	<b>15</b>	

## PCT REQUEST

Original (for SUBMISSION) - printed on 23.01.2003 11:28:24 AM

	Accompanying Items	paper document(s) attached	electronic file(s) attached
IX-8	Fee calculation sheet	✓	-
IX-11	Copy of general power of attorney	✓	-
IX-17	PCT-EASY diskette	-	Diskette
IX-19	Figure of the drawings which should accompany the abstract	1	
IX-20	Language of filing of the international application	English	
X	Signature of applicant, agent or common representative	 VAN DER VEER, Johannis, L. (Authorized Representative)	
X-1	Name (LAST, First)		
X-2	Capacity		

## FOR RECEIVING OFFICE USE ONLY

10-1	Date of actual receipt of the purported international application	24 JAN 2003 (24-01-03)
10-2	Drawings:	
10-2-1	Received	
10-2-2	Not received	
10-3	Corrected date of actual receipt due to later but timely received papers or drawings completing the purported international application	
10-4	Date of timely receipt of the required corrections under PCT Article 11(2)	
10-5	International Searching Authority	ISA/EP
10-6	Transmittal of search copy delayed until search fee is paid	

## FOR INTERNATIONAL BUREAU USE ONLY

11-1	Date of receipt of the record copy by the International Bureau	
------	--	--

Display device comprising a cathode ray tube

The invention relates to a display device comprising:

- a cathode ray tube having an electron gun for generating at least one electron beam and an outer conductive layer;
- a video amplifier for modulating the at least one electron beam;
- 5 - video processing circuitry for providing a video signal having a black level to the video amplifier, the video processing circuitry comprising black level controlling circuitry for controlling the black level of the video signal;
- a high-tension generator having output terminals; and
- a sensing circuit for sensing a black current level of the at least one electron beam
- 10 corresponding to the black level of the video signal and for feeding back information about the black current level to the black level controlling circuitry for stabilizing the black current level.

An embodiment of such a device is known from US 2002/0130965. The

15 known device has a sensing circuit having transistors, each transistor being connected to a respective one of the cathodes of the electron guns of the cathode ray tubes of a projection television system. The black level controlling circuitry inserts a level corresponding to a respective one of the black levels of each of the color components of the video signal in the color components of the video signal during one or more line periods within a vertical

20 blanking period. These black levels are transferred to the cathodes via the video amplifiers. The resulting black current levels of the electron beams are sensed at the cathodes by the sensing circuit and fed back to the black level controlling circuitry. Based on the resulting black current levels the black level controlling circuitry adjusts the black levels of the video signal, so as to ensure that the black levels of the video signal correspond with the black

25 current levels of the cathode ray tubes. In this way the described feedback loop stabilizes the black levels of the image on the screen of the cathode ray tubes. If, like mentioned in above example, more than one electron beam has to be controlled, the black level controlling circuitry generates sequentially, for example during successive lines, the black level for each of the electron beams to be controlled. In doing so, the sensing circuit may add the black

current levels of each of the cathodes into one signal, which contains, for example, in successive lines the values of the black current levels of the individually sensed electron beams. In case of a color cathode ray tube three cathodes are present in one tube. These cathodes have to be operated usually at a voltage level of about 200V. As a result, at least 3 transistors capable of withstanding about 200V are required for sensing the electron beams. It is a drawback that these transistors are expensive and increase the capacitive load of the video amplifiers, thereby deteriorating the frequency response of the video amplifiers.

It is an object of the invention to provide a display device of the kind described in the opening paragraph, which enables the presence of a relatively cheap sensing circuit.

The object is realized in that the sensing circuit is coupled to a node to which the outer conductive layer and one of the output terminals of the high-tension generator are coupled. As a result thereof, the black current level can be sensed at the anode side of the cathode ray tube instead of the cathode side. The voltage across the sensing circuit remains low in this case, for example in the range from 0V to 12V. So, the need for transistors in the sensing circuit that have to operate at a level of about 200V, is avoided, thereby allowing for a reduction of the cost of the sensing circuit. Moreover, the video response of the video amplifier improves, as there is no extra transistor, causing an additional capacitive load, required at the cathode for sensing the black current level. Finally, as there is no sensing circuit required between the video amplifiers and the cathode, the wire connection present between this cathode sensing circuit, which usually is located on a printed circuit board connected to the picture tube, and the video processing circuitry, which usually is present on a separate main printed circuit board, is avoided. The term "high-tension" denotes the voltage level at the anode of the cathode ray tube, which is in the order of magnitude of 25,000 V.

It is advantageous if the sensing circuit is coupled between the node and a reference voltage source. By the presence of a reference voltage source, the voltage range at the output of the sensing circuit can be adapted to match the operating range of the black level controlling circuitry.

In an embodiment the electron gun (G) is adapted for generating three electron beams and the black level controlling circuitry is adapted for allowing the sensing circuit to sequentially sense the black current levels of each of the three beams. This embodiment may have the same sensing circuit as an embodiment in which only one electron beam has to be sensed. The respective black currents having the respective black current levels of each beam

flow sequentially through the sensing circuit. The resulting sequential information is fed back to the black level controlling circuitry. As in this case three transistors having to operate at a level of about 200V for sensing the black current level at the cathodes can be avoided, a considerable cost saving is achievable.

5 It is advantageous if the sensing circuit comprises a current mirror circuit coupled between the node and the reference voltage source, an output of the current mirror circuit being coupled to the video processing circuitry. The mirror circuit ensures that the black current flowing through a main branch of the current mirror circuit is also flowing in a second branch of the circuit, which is coupled to the black level controlling circuitry. This  
10 allows that one end of the main branch is connected to a variable voltage. Such a variable voltage may be the result of a resistor connected between the reference voltage and the sensing circuit. In the case an electron gun is present for generating three beams, the total beam current of the three beams is flowing through this resistor, so the variable voltage is proportional to the total beam current. This variable voltage may be used in another feedback  
15 loop to control the average or peak value of the total beam current.

Japanese patent application 2002-099234 discloses a method of calibrating the black level, the cut-off level, by displaying sequentially the black level of each primary color on the full screen and measuring the beam current under these conditions. However, it is not disclosed how this detector is incorporated in a display device, neither is the circuitry of the  
20 detector disclosed.

These and other aspects of the display device of the invention will be further elucidated and described with reference to the drawings, in which:

Fig. 1 shows a schematic diagram of an embodiment of a display device  
25 according to the invention;

Fig. 2 shows waveforms of the video signal and feedback signal; and

Fig. 3 shows an embodiment of the sensing circuit.

The same references in different Figs. refer to the same signals or to the same elements performing the same function.

30 The display device shown in Fig. 1 has a cathode ray tube T, a video amplifier VA, video processing circuitry VP, a high-tension generator H, and a sensing circuit S. The tube T has an electron gun (G) for generating at least one electron beam. The cathode ray tube T may be a monochrome tube having an electron gun G with one cathode or a color tube

having an electron gun G with three cathodes. In Fig. 1 a tube T is shown having a gun (G) comprising three cathodes CR, CG, CB for generating three electron beams corresponding to, for example, a red, green and blue color. The tube T further has an internal high tension capacitance C which is formed by a conductive layer at the inner side of the tube connected to an anode AN of the tube T and an outer conductive layer AD at the outside of the tube opposite to the inner conductive layer. The video amplifier VA comprises three amplifier stages AR, AG, AB which receive respective color components VoR, VoG, VoB of a video signal Vo. The respective amplifier stages AR, AG, AB of the video amplifier VA drive the respective cathodes CR, CG, CB to modulate the corresponding electron beams flowing from the respective cathodes CR, CG, CB to the anode AN. The video processing circuitry VP comprises black level controlling circuitry BL for controlling the black level of the video signal Vo. In the embodiment shown in Fig. 1 each of the color components VoR, VoG, VoB have a respective black level BLR, BLG, BLB controllable by the black level controlling circuitry BC. The video processing circuitry VP provides the video signal Vo to the video amplifier VA. The high tension generator H has two output terminals: one terminal is connected to the anode AN and the other terminal is connected to the outer conductive layer AD via node X. So, the output terminals of the high-tension generator H and the high-tension capacitance C are forming a parallel coupling. The sensing circuit S is connected in series with the parallel coupling at node X. The sensing circuit is also connected to a node Y. Node Y is connected to a reference voltage V1 via a resistor R1. Parallel to the series connection of resistor R1 and reference voltage V1 is connected a capacitor C1. The sensing circuit S has an output connected to a feedback input FI of the black level controlling circuitry BL.

As can be seen in Fig. 1 the three electron beams originating from the cathodes CR, CG, CB all reach the same anode AN of the tube T. So, in other words, at the anode side a beam current IB is flowing, being the sum of the three electron beam currents. This current flows from ground potential via node Y through the sensing circuit S and high tension capacitance C to the anode AN. Any discharging of the high tension capacitance C by the beam current IB is compensated by recharging via the high tension generator H. The resulting recharging current flows in the loop formed by the parallel coupling of the high tension generator H and the high tension capacitance C and does not flow into node X. So, as between node Y and X only the beam current IB is flowing, the sensing circuit S can be positioned between these nodes X and Y.

The black level controlling circuitry BL receives a video input signal Vi, which, in the example of a tube T having electron beams for generating a red, green and blue



color, is composed of a red, green and blue color component. The DC level of each of the color components can be shifted by the black level controlling circuitry BL in dependence of a feedback signal FS received via a feedback input FI of the black level controlling circuitry BL. The purpose of the shifting is to ensure that the black level BLR, BLG, BLB of each of the color components VoR, VoG, VoB of the video signal Vo, present at the output of the black level controlling circuitry BL and applied to the cathode ray tube T via the video amplifier VA matches the respective black levels of the tube T. In this way the video signal Vo is rendered on the screen of the tube T with the correct black level. Moreover by matching the relative black levels of the color components VoR, VoG, VoB of the video signal Vo also a correct rendering of the colors is ensured.

Further the black level controlling circuitry BL inserts sequentially during a vertical flyback period VF, for example during a number of successive lines, a black level in each of the color components of the video-input signal Vi, resulting in waveforms as function of time t of the color components VoR, VoG, VoB of the video signal Vo as shown in Fig. 2. The inserted black levels of the respective color components VoR, VoG, VoB are indicated by BLR, BLG, and BLB respectively. During a time interval whereby in one of the respective color components VoR; VoG; VoB a black level BLR; BLG; BLB is inserted, the other color components VoR; VoG; VoB are having a blanking level BO below the black level BLR; BLG; BLB, so as to ensure that the corresponding electron beams are completely cut-off. So, the resulting beam current IB flowing through node X into the sensing circuit S comprises sequentially the black current levels IBR, IBG, IBB which may be detected sequentially by the sensing circuit S, resulting in a feedback signal FS of a similar shape as the beam current IB as shown in Fig. 2. The black level controlling circuitry BL uses the feedback signal FS to stabilize the black current levels IBR, IBG, IBB on a predetermined level by adapting the black level BLR, BLG, BLB of the respective color components VoR, VoG, VoB of the video signal Vo until the predetermined level is obtained for each of the color components VoR, VoG, VoB.

As it is desirable to detect also an average beam current value and/ or a peak beam current value, the resistor R1 is present between node Y and the reference voltage V1 as shown in Fig. 1. As a result the voltage on node Y may fluctuate dependent on the beam current. This voltage may be used in another feedback loop to limit the average and/ or peak beam current. The time constant applied for the averaging is determined by the RC-time of resistor R1 and capacitor C1.

As the sensing circuit S is connected via node Y to a fluctuating voltage, a special circuit configuration is required for the sensing circuit S to sense the beam current IB.

An embodiment of a suitable sensing circuit S is shown in Fig. 3. A first transistor Q1 has first main terminals, being an emitter and a collector connected to Node Y and Node X, respectively. The first transistor Q1 further has a first control terminal, being the base, connected to Node X. A second transistor Q2 has second main terminals, being an emitter and a collector connected to Node Y and to the feedback input FI, respectively. The second transistor Q2 further has a second control terminal, being the base, connected to the first control terminal. The described configuration of the first Q1 and second transistor Q2 is a current mirror. The beam current IB flowing through the main current path via the collector and emitter of the first transistor Q1 is "mirrored" in the second transistor Q2. So, through the second transistor Q2 a current flows from its emitter to its collector, being the output of the current mirror circuit, towards the feedback input FI, which is equal to the beam current IB.

It should be noted that the above-mentioned embodiments illustrate rather than limit the invention, and that those skilled in the art will be able to design many alternative embodiments without departing from the scope of the appended claims. For example, the invention may also be applied to a projection television system applying a separate monochrome cathode ray tube for each color, whereby the high tension capacitance C of each of the tubes are coupled in parallel to a common high tension generator H.

In the claims, any reference signs placed between parentheses shall not be construed as limiting the claim. Use of the verb "comprise" and its conjugations does not exclude the presence of elements or steps other than those stated in a claim. The article "a" or "an" preceding an element does not exclude the presence of a plurality of such elements. The invention may be implemented by means of hardware comprising several distinct elements, and by means of a suitably programmed computer. In the device claim enumerating several means, several of these means may be embodied by one and the same item of hardware. The mere fact that certain measures are recited in mutually different dependent claims does not indicate that a combination of these measures cannot be used to advantage.

## CLAIMS:

1. A display device comprising:
  - a cathode ray tube (T) having an electron gun (G) for generating at least one electron beam, and an outer conductive layer (AD);
  - a video amplifier (VA) for modulating the at least one electron beam;
  - 5 – video processing circuitry (VP) for providing a video signal (Vo) having a black level (BLR, BLG, BLB) to the video amplifier (VA), the video processing circuitry (VP) comprising black level controlling circuitry (BL) for controlling the black level (BLR, BLG, BLB) of the video signal (Vo);
  - a high-tension generator (H) having output terminals;
  - 10 – and a sensing circuit (S) for sensing a black current level (IBR, IBG, IBB) of the at least one electron beam corresponding to the black level (BLR, BLG, BLB) of the video signal (Vo) and for feeding back information about the black current level (IBR, IBG, IBB) to the black level controlling circuitry (BL) for stabilizing the black current level (IBR, IBG, IBB),
  - 15 the sensing circuit (S) being coupled to a node (X) to which the outer conductive layer (AD) and one of the output terminals of the high-tension generator (H) are coupled.
2. A display device as claimed in claim 1, wherein the sensing circuit (S) is coupled between the node (X) and a reference voltage source (V1).
- 20 3. A display device as claimed in claim 1, wherein the electron gun (G) is adapted for generating three electron beams; and the black level controlling circuitry (BL) is adapted for allowing the sensing circuit (S) to sequentially sense the black current levels (IBR, IBG, IBB) of each of the three beams.
- 25 4. A display device as claimed in claim 1, wherein the sensing circuit (S) comprises a current mirror circuit coupled between the node (X) and the reference voltage source (V1), an output of the current mirror circuit being coupled to the video processing circuitry (VP).

5. A display device as claimed in claim 4, wherein the current mirror circuit comprises:

- a first transistor (Q1) having a pair of first main terminals and a first control terminal, the first main terminals being coupled between the node (X) and the reference voltage source (V1), the first control terminal being coupled to the node (X); and
- a second transistor (Q2) having a pair of second main terminals and a second control terminal, the second control terminal being coupled to the first control terminal, one of the second main terminals being coupled to the reference voltage source (V1) and the other of the second main terminals being coupled to the video processing circuitry (VP).

## ABSTRACT:

The display device has a cathode ray tube (T), which has an electron gun (G) for generating an electron beam and an outer conductive layer (AD). A video processing circuitry (VP) provides a video signal (Vo) having a black level (BLR, BLG, BLB) to a video amplifier (VA) for modulating the electron beam. The video processing circuitry (VP) has  
5 black level controlling circuitry (BL) for controlling the black level (BLR, BLG, BLB) of the video signal (Vo). A sensing circuit (S) senses a black current level of the electron beam corresponding to the black level of the video signal (Vo) and feeds back information about the black current level to the black level controlling circuitry (BL) for stabilizing the black  
10 current level. The sensing circuit (S) is coupled to a node (X) to which the outer conductive layer (AD) and one of the output terminals of a high-tension generator (H) are coupled.

Fig. 1

CONFIRMATION COPY




FIG. 1

2/3




FIG. 2

3/3




FIG. 3